



US 20210206214A1

(19) **United States**(12) **Patent Application Publication**  
**McCoy et al.**(10) **Pub. No.: US 2021/0206214 A1**(43) **Pub. Date: Jul. 8, 2021**(54) **FIFTH WHEEL HITCH MOUNTING SYSTEM****B60D 1/48** (2006.01)**F16B 2/18** (2006.01)(71) Applicant: **HORIZON GLOBAL AMERICAS**  
**INC.**, Plymouth, MI (US)(52) **U.S. Cl.**CPC ..... **B60D 1/52** (2013.01); **F16B 2/185**  
(2013.01); **B60D 1/485** (2013.01); **B60D**  
**1/015** (2013.01)(72) Inventors: **Richard W. McCoy**, Granger, IN (US);  
**Brian Ward**, Swartz Creek, MI (US)(21) Appl. No.: **17/149,882**(22) Filed: **Jan. 15, 2021****Related U.S. Application Data**(63) Continuation of application No. 16/105,267, filed on  
Aug. 20, 2018, now Pat. No. 10,894,454, which is a  
continuation of application No. 15/356,943, filed on  
Nov. 21, 2016, now Pat. No. 10,052,924, which is a  
continuation of application No. 14/919,260, filed on  
Oct. 21, 2015, now Pat. No. 9,499,017.(60) Provisional application No. 62/066,592, filed on Oct.  
21, 2014.**Publication Classification**(51) **Int. Cl.****B60D 1/52** (2006.01)**B60D 1/01** (2006.01)

(57)

**ABSTRACT**

A hitch mount configured to be selectively attached to a vehicle, the vehicle having an under bed hitch mounting system is shown and described. The hitch mount may include at least one transverse member, at least one longitudinal member attached with the at least one transverse member, the at least one longitudinal member including first and second apertures, the first and second apertures of different size, and first and second fastening devices configured to selectively engage the under bed hitch mounting system and the first and second apertures, respectively. The hitch mount may also include first and second biasing members operatively engaged with the first and second fastening, the biasing members applying a load against the under bed hitch mounting system, and first and second handles pivotally and rotatably attached with the first and second fastening devices, the handles having a camming surface configured to engage the first and second biasing members.

